

VirGin LVT

Technical Data Sheet - Herringbone (5mm)

Type & Composition		PVC Laminated Floor Covering
Water Proof		100 % Water Proof
Application		Commercial , Residential
Surface Treatment		PU & Anti-bacterial, Per Design
Profile		Click Lock (Unilin Click)
Size (mm)	EN 427	128 x 610
Total Thickness (mm)	EN 4.3	5
Wear Layer Thickness (mm)	EN 429	0.50 / 0.55
Fire Rating	EN 13501-1	B ft - S1
	Mekel Bumer Test	Pass
Heat Stability	KSM 3802	0.50 / 0.55mm / 0.01 (80 °C + 2 °C, 6hr/hr)
Slip Resistance	BS 7976-2	PVC Laminated Floor Covering RZ Surface Roughness : Moderate
Residual Indentation	EN 433	≤ 0.10mm
Color Fastness	ISO 105-B02	≥ 6
Dimensional Stability	EN 434	≤ 0.25 %
Flexibility	EN 435	No Crack was found
Electrical Behavior	EN 1081	Pass

VirGin Tiles - Glueless Luxury Vinyl Tiles

◆ Individual Glass Fiber Layer	◆ No Glue / No Underlay	◆ Organic-Inorganic Hybrid Antimicrobial Technology
◆ Extra Flexibility Over Any Surfaces	◆ 4 Side Micro Bevel	◆ Waterproof / Easy Clean / Easy Installation
◆ 0.5/0.55mm Micro- Ceramic Wear Layer	◆ 2 Coats PU	◆ Fire / Slip / Oil / Stain Resistant

